

MINI-TROL®


Composite Water Hammer Arrestor



Shock Suppression. Simplified.™



MINI-TROL®



Mini-Trol water hammer arrestors absorb shock to eliminate noisy pipes and pressure surges caused by fast-acting valves. Unlike piston-type suppressors, Mini-Trol contains no mechanical parts or seals; resulting in a maintenance-free shock absorber that provides years of reliable protection.

360° Air Cell

- Proprietary, sealed design never requires charging.
- · Superior water hammer capacity.
- Entire air cell surface absorbs energy for greater protection.

Advanced Composite Material

- Durable and corrosion proof.
- · Impact resistant polymer.

Worry-Free Longevity

- · Patent-pending technology eliminates sliding parts.
- · No pistons or o-rings to wear out.

Specifications

Type: PDI Size "A" Diameter: 3-3/8"

Height: 4"

Connection: 1/2" NPTM

Maximum Supply Pressure: 80 psi Maximum Working Pressure: 150 psi Maximum Intermittent Temperature: 180° F


Air Cushion: Permanent Fixture Units: 1-11 ASSE 1010 Listed

Typical Installations




Single Pipe Fixture

- Toilets
- Hose Bibbs
- Flushometers




Hot/Cold Fixture

- Single handle sinks
- Shower valves
- Utility sinks



Fast Acting Valve

- Dishwashers
- Washing Machines
- Icemakers



Branch Line

- Multi-fixture runs
- Restrooms
- Manifolds







1400 Division Road, West Warwick, RI USA 02893 T: 800.426.8765 F: 800.293.1519 www.amtrol.com



